

according to Regulation (EC) No 1907/2006

# **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP CEMENT SC 2000

## Art.-No.

525 1557, 525 2025, 525 2027, 525 2029, 525 2050, 525 2053, 525 2064, 525 2130, 525 2153, 525 2160, 525 2161, 525 2163, 525 2165, 525 2173, 525 2191, 525 2193, 525 2194, 525 2196, 525 2247, 525 2249, 525 4003, 525 4006, 525 4010, 525 4024, 525 4027, 525 4034, 525 4043, 525 4041, 525 4058

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

adhesive

## 1.3. Details of the supplier of the safety data sheet

Company name:	REMA TIP TOP AG
Street:	Gruber Strasse 65
Place:	D-85586 Poing
Telephone:	+49 (0) 8121 / 707 - 100
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 24

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Respiratory or skin sensitisation: Skin Sens. 1
Germ cell mutagenicity: Muta. 2
Carcinogenicity: Carc. 1B
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing genetic defects.
May cause cancer.
Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### Regulation (EC) No. 1272/2008

## Hazard components for labelling Trichloroethylene Colophonium Danger

Signal word:

Revision No: 2,2

according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

**Pictograms:** 

Product code: 00156-0002

Page 2 of 10



### Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

ecautionaly statement	.5
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P273	Avoid release to the environment.

### Special labelling of certain mixtures

Restricted to professional users.

## 2.3. Other hazards

Not known.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

Chemical characterization Preparation with trichloroethylene

#### Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regula	.P]			
79-01-6	Trichloroethylene				
	201-167-4	602-027-00-9	01-2119490731-36		
	Carc. 1B, Muta. 2, Skin Irrit. 2, Ey H341 H315 H319 H317 H336 H4		SE 3, Aquatic Chronic 3; H350		
1314-13-2	Zinc oxide				
	215-222-5	030-013-00-7	01-2119463881-32		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410				
8050-09-7	Colophonium			< 2,5 %	
	232-475-7	650-015-00-7	01-2119480418-32		
	Skin Sens. 1; H317				

Full text of H and EUH statements: see section 16.

## **Further Information**

SVHC substance [Regulation (EC) No 1907/2006, Article 57]: Trichloroethylene



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 3 of 10

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours. In the event of symptoms refer for medical treatment.

#### After contact with skin

Wash off immediately with soap and plenty of water. Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

#### After ingestion

Induce vomiting only upon the advice of a physician. Attention. Beware, danger of aspiration. Summon a doctor immediately. Immediately give plenty of water, if possible charcoal slurry.

## 4.2. Most important symptoms and effects, both acute and delayed

### May cause cancer. May cause drowsiness or dizziness. May cause an allergic skin reaction. Causes serious eye irritation. Causes skin irritation. Suspected of causing genetic defects.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray. Product does not burn, fire-extinguishing activities according to surrounding.

#### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide and carbon dioxide Chlorine and traces of phosgene. Hydrogen chloride gas.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

## Additional information

Keep away from heat and sources of ignition.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 4 of 10

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Care for thoroughly room ventilation, if necessary suck off at workplace. Avoid contact with skin, eyes and clothing.

## Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

### Advice on storage compatibility

Incompatible with: Oxidizing agents Aluminium powder Alkaline metals and earth alkaline metals. Alkaline leaches

## Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

adhesive

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 5 of 10

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL
79-01-6	Trichloroethylene	100	550		TWA (8 h)	WEL
		150	820		STEL (15 min)	WEL

## 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

## Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

### Hand protection

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Long sleeved clothing (EN 368).

### **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Liquid Different Sweetish	
		Test method
Changes in the physical state		
Initial boiling point and boiling range:		approx. 90 °C
Flash point:		n.a. *)
Lower explosion limits:		7,9 vol. %
Upper explosion limits:		
Ignition temperature:		410 °C
Vapour pressure: (at 20 °C)		77 hPa
Density:		1,45 g/cm <sup>3</sup>



according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT SC 2000

Revision date: 19.07.2017	Product code: 00156-0002	Page 6 of 10
Water solubility: (at 20 °C)	Immiscible	
Viscosity / dynamic:	3000 mPa·s	
Vapour density:	4,54	
Solvent content:	< 90 %	
0.2 Other information		

### 9.2. Other information

"\*) According to PTB instructions, trichloroethylene has no flashpoint; however, vapour and air mixtures are flammable under a stronger energy influx."

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Reactions with alkali metals. Reactions with earth alkali metals. Reactions with oxidizing agents.

#### 10.4. Conditions to avoid

Above 120°C, a thermic decomposition may take place.

#### 10.5. Incompatible materials

Alkaline metals and alkaline earth metals., Bases., oxidizing agents, Aluminium powder

#### 10.6. Hazardous decomposition products

Chlorine and traces of phosgene. Hydrogen chloride gas Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

Trichloroethylene LD50/oral/rat: 5400 mg/kg LD50/dermal/rabbit: > 2000 mg/kg LC50/inhalation/rat: 12500 ppm/4h

## Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (Trichloroethylene; Colophonium)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Trichloroethylene) May cause cancer. (Trichloroethylene) Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Trichloroethylene)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 7 of 10

## Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### Practical experience

#### Other observations

Components of the product may be absorbed into the body through the skin. (skin absorption).

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Effects of breathing high concentrations of vapour may include:

Headache, dizziness, weakness, unconsciousness.

Hazard of lung oedema.

Skin contact or inhalation of solvents contained in this product may cause irritation of skin, eyes and mucous membranes.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Trichloroethylene LC50/Pimephales promelas/ 96 h = 42,4 mg/l EC50/Daphnia magna/48 h = 20,8 mg/l EC50/Algae/96 h = 36,5 mg/l Zinc oxide EC50/Selenastrum capricornutum/72 h = 0,17 mg/l

Toxic to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

Trichloroethylene Biodegradable (OECD): 2,4% (14 d) [OECD 301C] Not readily biodegradable.

### 12.3. Bioaccumulative potential

Trichloroethylene Low bio-accumulation can be estimated because of low log Po/w. (Log Pow: 2,53)

### 12.4. Mobility in soil

Trichloroethylene High mobility in soil.

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## 12.6. Other adverse effects

Severe hazard to waters

## **Further information**

Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

## Waste disposal number of waste from residues/unused products



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 8 of 10

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

## Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 1710
14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution
14.3. Transport hazard class(es):	6.1
14.4. Packing group:	III
Hazard label:	6.1
	6
Classification code:	T1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category: Hazard No:	2
Tunnel restriction code:	60 F
	-
Other applicable information (land transp HAZCHEM: 2Z	δοπ)
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1710
<u>14.1. UN number:</u> 14.2. UN proper shipping name:	UN 1710 TRICHLOROETHYLENE, Solution
14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution
14.2. UN proper shipping name: 14.3. Transport hazard class(es):	TRICHLOROETHYLENE, Solution 6.1
14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group:	TRICHLOROETHYLENE, Solution 6.1 III
14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group:	TRICHLOROETHYLENE, Solution 6.1 III
14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label:	TRICHLOROETHYLENE, Solution 6.1 III 6.1
14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Classification code:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1
14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Classification code: Limited quantity:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg
14.2. UN proper shipping name:14.3. Transport hazard class(es):14.4. Packing group:Hazard label:Classification code:Limited quantity:Excepted quantity:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg
14.2. UN proper shipping name:   14.3. Transport hazard class(es):   14.4. Packing group:   Hazard label:   Classification code:   Limited quantity:   Excepted quantity:   Marine transport (IMDG)   14.1. UN number:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg E1
14.2. UN proper shipping name:   14.3. Transport hazard class(es):   14.4. Packing group:   Hazard label:   Classification code:   Limited quantity:   Excepted quantity:   Marine transport (IMDG)   14.1. UN number:   14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg E1 UN 1710
14.2. UN proper shipping name:   14.3. Transport hazard class(es):   14.4. Packing group:   Hazard label:   Classification code:   Limited quantity:   Excepted quantity:   Marine transport (IMDG)   14.1. UN number:   14.2. UN proper shipping name:   14.3. Transport hazard class(es):	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg E1 UN 1710 TRICHLOROETHYLENE SOLUTION 6.1
14.2. UN proper shipping name:   14.3. Transport hazard class(es):   14.4. Packing group:   Hazard label:   Classification code:   Limited quantity:   Excepted quantity:   Marine transport (IMDG)   14.1. UN number:   14.2. UN proper shipping name:	TRICHLOROETHYLENE, Solution 6.1 III 6.1 T1 5 L / 30 kg E1 UN 1710 TRICHLOROETHYLENE SOLUTION



## according to Regulation (EC) No 1907/2006

	TIP TOP CEMENT SC 2000	
Revision date: 19.07.2017	Product code: 00156-0002	Page 9 of 10
	6	
Marine pollutant:	Yes	
Limited quantity:	5 L / 30 kg	
Excepted quantity:	E1	
EmS:	F-A, S-A	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1710	
14.2. UN proper shipping name:	TRICHLOROETHYLENE SOLUTION	
14.3. Transport hazard class(es):	6.1	
<u>14.4. Packing group:</u>	III	
Hazard label:	6.1	
	6	
Limited quantity Passenger:	2 L	
Passenger LQ:	Y642	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:	655	
IATA-max. quantity - Passenger:	60 L	
IATA-packing instructions - Cargo:	663	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	yes	¥2

## 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practices.

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>EU regulatory information</b> Authorisations (REACH, annex XIV): Trichloroethylene	
Restrictions on use (REACH, annex XVII): Entry 28: Trichloroethylene	
2004/42/EC (VOC):	< 90 %
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water contaminating class (D):	3 - highly water contaminating



according to Regulation (EC) No 1907/2006

## **TIP TOP CEMENT SC 2000**

Revision date: 19.07.2017

Product code: 00156-0002

Page 10 of 10

## Additional information

Consider Chemical prohibition regulation.

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm

ISO = International Organization for Standardization

- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic
- vPvB = Very Persistent and very Bio-accumulative
- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)