SAFETY DATA SHEET

1. Identification

Product identifier Lectra Clean® Heavy Duty Electrical Parts Degreaser

Other means of identification

No. 02018 (Item# 1003177) **Product Code** Recommended use Energized electrical cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name 885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone

215-674-4300 **General Information Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B

Sensitization, skin Category 1B Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic

skin reaction. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer. Toxic

Category 2

to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Response

Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned:

Get medical advice/attention. Collect spillage.

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high

temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
tetrachloroethylene	perchloroethylene	127-18-4	90 - 100
carbon dioxide		124-38-9	1 - 3
decafluoropentane	HFC 43-10mee	138495-42-8	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. If skin

irritation or rash occurs: Get medical advice/attention.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Get Ingestion

medical attention if symptoms occur.

reaction. Dermatitis. Rash.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry chemical, CO2, or water spray.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

General fire hazards Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Protect from sunlight. Store in a well-ventilated place. Store in cool place. Exposure to high temperature may cause can to burst. Store away from incompatible materials (see Section 10 of the SDS).

1/-1...

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
US. OSHA Table Z-2 (29 CFR 1910.1000)		
Components	Type	Value
tetrachloroethylene (CAS 127-18-4)	Ceiling	200 ppm
,	TWA	100 ppm
US. ACGIH Threshold Limit Values		
Components	Туре	Value
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
•	TWA	5000 ppm

US. ACGIH Threshold Limit Valu Components	ues Type	Value	
tetrachloroethylene (CAS 127-18-4)	STEL	100 ppm	
,	TWA	25 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
tetrachloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*
·	3 ppm	Tetrachloroethy lene	End-exhaled air	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - Minnesota Haz Subs: Skin designation applies

tetrachloroethylene (CAS 127-18-4)

Skin designation applies.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eve wash facilities and emergency shower should be available when handling this product. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Nitrile. Viton/butyl. Polyvinyl alcohol (PVA). Silver Shield® Hand protection

Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol. Color Colorless. Odor Irritating. **Odor threshold** 50 ppm Not available.

Melting point/freezing point -8.1 °F (-22.3 °C) estimated Initial boiling point and boiling 250.3 °F (121.3 °C) estimated

range

Flash point None (Tag Closed Cup) **Evaporation rate** Very fast. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

(%)

Not applicable.

1333.3 hPa estimated Vapor pressure

Vapor density 5.76 (air = 1)Relative density 1.61 estimated Not available. Solubility (water) Not available. Partition coefficient (n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Viscosity (kinematic) Not available. 97.7 % estimated Percent volatile

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. When exposed to extreme heat or

hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen

fluoride, hydrogen chloride, and possibly phosgene. Strong oxidizing agents. Strong acids. Strong bases.

Incompatible materials

Hazardous decomposition

products

Hydrogen fluoride. Hydrogen chloride. Trace amounts of chlorine and phosgene. Carbon oxides.

Halogenated materials. Carbonyl halides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May cause drowsiness and dizziness. Headache. Nausea,

vomiting.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

Information on toxicological effects

None known. **Acute toxicity**

Test Results Components **Species**

decafluoropentane (CAS 138495-42-8)

Acute **Dermal**

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 11058 mg/kg, 4 hours calculated

Oral

LD50 Rat > 5000 mg/kg

Material name: Lectra Clean® Heavy Duty Electrical Parts Degreaser

Components Species Test Results

tetrachloroethylene (CAS 127-18-4)

<u>Acute</u>

Dermal

LD50 Rabbit > 3228 mg/kg

Oral

LD50 Rat 2629 mg/kg

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye Causes eye irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

tetrachloroethylene (CAS 127-18-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

tetrachloroethylene (CAS 127-18-4)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityToxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components		Species	Test Results	
decafluoropentane (C.	AS 138495-42-8)			
Aquatic				
Acute				
Crustacea	EC50	Water flea (Daphnia magna)	11.7 mg/l, 48 hours	
Fish	LC50	Zebra danio (Danio rerio)	13 mg/l, 96 hours	
tetrachloroethylene (C	AS 127-18-4)			
Aquatic				
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4.73 - 5.27 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

decafluoropentane 2.7. Pow at 20 °C

tetrachloroethylene 2.88

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal of waste from residues / unused products This material and its container must be disposed of as hazardous waste. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose in accordance with all applicable regulations.

D039: Waste Tetrachloroethylene Hazardous waste code

F001: Waste Halogenated Solvent - Spent Halogenated Solvent Used in Degreasing

F002: Waste Halogenated Solvent - Spent Halogenated Solvent

US RCRA Hazardous Waste U List: Reference

tetrachloroethylene (CAS 127-18-4)

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name

Aerosols, poison, Limited Quantity

Transport hazard class(es)

2.2 6.1(PGIII) Subsidiary risk Label(s) 2.2, 6.1 Packing group Not applicable.

Special precautions for user Forbidden from transportation by air.

Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN number**

UN proper shipping name Transport hazard class(es)

Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III

2.2 Class Subsidiary risk 6.1(PGIII) Packing group Not applicable.

ERG Code

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es)

Class

Subsidiary risk 6.1(PGIII) Packing group Not applicable.

Environmental hazards

No. Marine pollutant F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

decafluoropentane (CAS 138495-42-8) 1.0 % One-Time Export Notification only.

SARA 304 Emergency release notification

Not regulated.

Material name: Lectra Clean® Heavy Duty Electrical Parts Degreaser No. 02018 (Item# 1003177) Version #: 04 Revision date: 11-01-2017 Issue date: 07-23-2014

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

tetrachloroethylene (CAS 127-18-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

tetrachloroethylene (CAS 127-18-4) Listed.

CERCLA Hazardous Substances: Reportable quantity

tetrachloroethylene (CAS 127-18-4) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

tetrachloroethylene (CAS 127-18-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes Delayed Hazard - Yes **Hazard categories** Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

tetrachloroethylene (CAS 127-18-4)

US. New Jersey Worker and Community Right-to-Know Act

No

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4) **US. Massachusetts RTK - Substance List**

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

US. Rhode Island RTK

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

tetrachloroethylene (CAS 127-18-4) Listed: April 1, 1988

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Consumer products

Not regulated

(40 CFR 59, Subpt. C) State

Consumer products

This product is regulated as an Energized Electrical Cleaner for the following states: California, Connecticut, Delaware, District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia. It is for energized equipment use only. It is not to be used for motorized vehicle maintenance or their parts. This product is compliant for use in all 50 states.

0 % VOC content (CA) VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

07-23-2014 Issue date 11-01-2017 **Revision date** Prepared by Allison Yoon

Version # 04

Further information CRC # 863A/1002837

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 0 Instability: 0

NFPA ratings



Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

This document has undergone significant changes and should be reviewed in its entirety. **Revision Information**

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).