



G. BESLUX WHITE BEARING GREASE

WHITE GREASE FOR BEARINGS

DESCRIPTION

Load resistant white lithium grease with EP additives and white solid lubricants.

APPLICATION

G. BESLUX WHITE BEARING GREASE will be used whenever a clean non staining water resistant lubricant with good EP-properties is needed, i. e. in the paper, textile industry, graphic, arts, food industry, taps, etc.

PROPERTIES

- Wide range of operating temperatures.
- Water resistant.
- Resists heavy loads.
- Long life and efficiency.
- White, clean, non-contaminant.

WAY TO USE

The first application will be direct onto the clean bearing without exceeding half housing capacity.

For further reagreasing, level with the necessary quantity without exceeding half bearing capacity. Applied manually or with proper greaser.

CAUTIONS

- The usual ones when handling and using lubricants.
- Avoid excess of grease as well as too frequent regreasing.
- Keep the can closed to avoid contamination.
- Do not mix with different nature greases.

PHYSICAL - CHEMICAL CHARACTERISTICS

Colour	White
Thickener, soap type	Lithium
Base oil nature	Mineral
Penetration 60W, 25°C, (0,1mm)	265-295
NLGI Consistency class	Grade 2
Drop point, (°C)	Min. 180
4 ball test, welding load, (kg)	Min. 300
EMCOR corrosion test	Max. 1
Water resistant, 90°C	Max. 1
Operating temperatures, (°C)	-30 to 120